

# AFO-20

## AirFlow Optimizer Fan Package

### Features:

- Variable frequency drive (VFD)
- Pressure transducer
- Tubeaxial booster fan & motor

### Benefits:

- Maintains optimal airflow minimizing dry time
- Corrects dryer inefficiencies / conserves energy
- Fully automated (after setup)

### Utility Requirements:


- 208v or 480v (specify); 60 Hz; 3-phase
- Independent electrical source required

### Fan Specifications:

- Drive: Belt
- Motor: 7-1/2hp; 1,750 rpm
- Max BHP: 6.88
- Fan RPM: 1,013
- Sones @ 0.250-in. SP @ 5' - 66
- Motor enclosure: enclosed / fan cooled
- Motor height: 12-1/2-inch
- Shaft diameter: 1-7/16-inch
- Blades: 5; aluminum
- FLA: 19.8-17.9/9.0
- Max inlet temp: 200 deg F
- Max ambient temp: 104 deg F
- Bearing: ball
- Mounting: vertical/horizontal
- Housing: steel; baked enamel finish

### CFM


- @ 0.000-in. SP - 29,150
- @ 0.125-in. SP - 28,410
- @ 0.250-in. SP - 27,610
- @ 0.500-in. SP - 25,900
- @ 0.750-in. SP - 23,960
- @ 1.000-in. SP - 21,775
- @ 1.250-in. SP - 18,120



AFO - SERIES



Variable Frequency Drive, Fan, & Transducer



### Dimensions

- A: 45-3/4"
- B: 25-1/8"
- C: 42-1/2"
- D: 32"
- E: 9/16"

INLINE SPACE SAVER TYPICAL INSTALLATION WITH AIRFLOW OPTIMIZER OR BOOSTER FAN

